

Daylight wall pack provides excellent perimeter and security lighting. EncapLED module with patent-pending heat sink and optic design achieves high efficacy and precise light distribution. The lightweight, low footprint aluminum fixture is easy to install and brighter than any other products in the market. This design allows for simple surface mount installation and easily replaces 70-400W HPS or Metal Halide systems.

### Feature Highlight

- Philips Rebel chips
- Up to 115 lm/W efficacy at 5000K
- Patent-pending EncapLED module for superior cooling and durability
- Wide range of wattage selections from 10W to 60W
- Light weight aluminum housing
- CETL/CUL, ROHS, IP65 rated and DLC Listed
- Five year warranty



### Optical Specification

- Color temperature from 2700K to 6000K
- CRI 70

### Electrical Specification

- Power input: 120-277V, 347 or 480V optional
- Power factor >90
- UL listed driver
- Optional for 0-100% dimming, motion sensor or smart controls to optimize energy savings with automatic scheduling

### Mechanical Specification

- Aluminum Housing: 10" x 6" x 4"
- Finishes: Bronze, Black, Silver, White

Model #	System Wattage	Lumens at 5000K @700mA	Replacement HPS/MH Wattage
DL-WP-10W	10	1050	70W
DL-WP-20W	20	2150	70W-150W
DL-WP-30W	30	3225	150W-175W
DL-WP-40W	40	4300	175W-250W
DL-WP-50W	50	5375	250W-400W
DL-WP-60W	60	6450	400W

### Order Information

Model #	Color Temperature	Lens Type	Finish	Accessories	Voltage
DL-WP Wattage (10W - 60W)	5000K 4000K 3500K (Special Order) 3000K (Special Order)	III	Bronze (BR) Black (BL) Silver (SL) White (WH)	None (N) Photo Cell (P) Dimmable (D)	120-277V 347V 480V

Order Example: DL-WP-40W-5000-III-BRN-N-277V